

## **QUOTE REQUEST FORM**

This form is the first step to creating your customized Bally Walk-In Cooler/Freezer with up to 3 compartments. (If your Walk-In requires more than 3 compartments, you do not need to fill out the form just email us or call 1-800-24BALLY.) Please fill out this form, adding any comments or questions, and email it to sales@ballyrefboxes.com.

A Bally representative will contact you with information and help you find a dealer in your area.

Name:		Email:				
Business Name:		Project Name:				
Address:		City:	State Zip			
Phone:		Fax:				
<b>OVERALL DIMENSI</b>	ONS of W	<b>VALK-IN</b> □ 4" Panel □ 5" Panel □ 6" Panel				
Estimated LENGTH:	Estimated WIDTH:		Estimated HEIGHT:			
*Choose from: 5'10", 6'3¾", 6'9½", 7'3¼", 7'9", 8'2¾", 8'8½", 9'2¼", 9'8", 10'1¾", 10'7½", 11'1¼", 11'7", 12'0¾", 12'6½", 13'0¼", 13'6", 14'5½", 15'5", 16'4½", 17'4", 18'3½", 19'3", 20'2½". Longer buildings are available in additional 5¾" increments.	7′9″, 8′2¾″, 8′8½″, 10′7½″, 11′1¼″, 1 13′0¼″, 13′6″, 14	0", 6'3¾", 6'9½", 7'3¼", 9'2¼", 9'8", 10'1¾", 1'7", 12'0¾", 12'6½", '5½". Longer build- in additional 11½"	4", 9'8", 10'1¾", ( <i>Single length verticals</i> ) 12'0¾", 12'6½", Taller buildings are available in additiona Longer build- 12" increments, with stacked vertical pan			
	. 🗆 .		Height of Building (if against one):			
Number of Compartments? (Check one)	Indoor: On Grade or Depression		———— <i>"</i>			
1	Outdoor: Free Standing Against Existing Building Illation Site: City & State:		Number of Walls Size x			
H	Dimensions:  Cooler:  Lx W  Freezer:  Lx W	x H	Hand sketch of the cooler/freezer			
Comments: For Bally Use Only:						
	Othe	Price:er Options:eght Total:				
Exterior Finish: (Check one)  Stucco-embossed Galvalume Smooth White galvanized ste Stainless steel Stucco-embossed aluminum Stucco-embossed White alum Stucco-embossed Sand-tan embossed Stainless	eel n minum galvanized steel vanized steel	☐ Stucco-em☐ Smooth Wh☐ Stainless st☐ Stucco-em☐ Stucco-em☐ Stucco-em☐ Smooth Wh	Interior Finish: (Check one)  Stucco-embossed Galvalume steel Smooth White galvanized steel Stainless steel Stucco-embossed aluminum Stucco-embossed White aluminum Stucco-embossed White galvanized steel Smooth White aluminum Embossed Stainless			

FLOORS		Floor Types: (Check one)  Less Floor  w/ Floor  w/ Floor—Less Floor  Light Use—Foot Traffic  Medium Use—Hand Truck or Small Cart  Heavy Duty—Structurally Reinforced (Keg or Pallet Jack & Queen Mary)			Floor Panel Finishes: (Check one)  3/16" Aluminum Diamond Tread Overlay  100 ga. Smooth Aluminum  16 ga. Stainless Steel Rigidized Aluminum Diamond Pattern  1/8" Aluminum Diamond Tread Rigidized Stainless Steel Diamond Pattern  16 ga. Galvanized Steel (Non NSF - to be used under any NSF approved Overlay)  Extra Overlay: 3/16" Diamond Tread				
	MF ne	S Interior Exterior		l		Options: (Check or of w/ tapered insu		n	
	Door 1			Door Options:  Observation Window in Entrance Door: 14" x 14"  Deadbolt Handle Latch: (K27C)  Strip Curtain(s)					
DOORS	Door 2	Width: Choose from: 30", 36", 42", 48", 54", 60"	Height: Choose from: 66", 78", 84"			Super Doors (1/8" Diamondtread kickplate on both sides, 3 <sup>rd</sup> hinge. Standard Sizes; included unless noted)			
	Door 3	Width: Choose from: 30", 36", 42", 48", 54", 60"	Hei	Height: Choose from: 66", 78", 84"		Glass Display Doors:  Number of Doors: Size: x			
	Ad	Additional Doors:			Sliding Door: Qty Size:x Slide Direction: Left Right				
				ACCE	SS	ORIES			
Tressure Heller Fore (required for freezers)			Yes	al Lighting: S No 4' LED Other		Alarm Systems:  Modularm 75L C WEISS  Other: Please specify			
REFRIGERATION SYSTEMS Storage Only Product Load									
nt 1	Conde Conde Ir O	ation (Choose one): ooler Freezer nsing Unit: ndoor Remote outdoor Air-Cooled Remot elf-Contained (PT-Unit)		Condensii  Indo  Outo	er [ ng Un oor Rei door <i>A</i> Conta	Freezer it:	Compartment 3	Application (Choose one):  Cooler Freezer  Condensing Unit:  Indoor Remote  Outdoor Air-Cooled Remote  Self-Contained (PT-Unit)	

Notes: For line sets ≤ 75'

 ${\it SmartVap+Evaporator\ Controls\ are\ Standard\ at\ Bally}.$